

Firebox M470, M570 & M670

Up to 34 Gbps firewall throughput, up to 5.4 Gbps UTM throughput

KEEP PACE WITH EXPLOSIVE GROWTH IN ENCRYPTED TRAFFIC

Firebox® M470, M570 & M670 firewalls are specifically engineered for midsize and distributed enterprises that are struggling to effectively and affordably secure networks in the face of explosive growth in bandwidth rates, encrypted traffic, video use, and connection speeds. What's more, the ability to add network modules for greater port density gives you the flexibility to adapt as the network grows and evolves.







M470

Optional Modules Choose the network

interface modules that support your ideal M470, M570 or M670 deployment









WatchGuard is nice and easy to use and has solved all our problems. Our security has increased dramatically and has made my life a lot simpler. I couldn't ask for better.

~ Jamie Stables, Desktop Support Analyst, Brompton

TOTAL NETWORK PROTECTION

Every network needs a full arsenal of scanning engines to protect against spyware, viruses, malicious apps, data leakage, botnets and more. WatchGuard's award-winning network security platform not only provides the most complete suite of unified security controls on the market today, but we have consistently been the first to offer solutions for addressing new and evolving network threats including ransomware and advanced malware.

EASILY MANAGE MANY APPLIANCES

Typically deployed at the corporate headquarters, these appliances serve as the "hub" appliance, responsible for centrally managing and securing all communications between the head office and all remote employee and small business sites. WatchGuard Dimension, which is included at no additional cost, provides a suite of big data visibility and reporting tools that instantly identify and distill key network security threats, issues and trends, accelerating the ability to set meaningful security policies across the entire network.


FUTURE-PROOF YOUR NETWORK

Network environments are more diverse than ever, offering a vast array of options to choose from. With Firebox M470, M570, and M670, IT pros can customize their port configuration with expansion modules to meet current needs, while ensuring the flexibility to adapt as their network evolves. Firebox M470, M570, and M670 include a single slot for an expansion module, with options for 8 x 1 Gb fiber, 4 x 10 Gb fiber, or 8 x 1 Gb copper.

FFATURES & BENFFITS

- Up to 34 Gbps firewall throughput. Turn on all security scanning engines and still see up to an amazing 5.4 Gbps throughput.
- All logging and reporting functions included with purchase, with over 100 dashboards and reports including PCI and HIPAA.
- · Gain critical insights about network security, from anywhere and at any time, with WatchGuard Dimension.
- Customize your port configuration to meet current needs, knowing you have the flexibility to adapt as the network evolves. This is how to future-proof your network and eliminate costly rip-and-replace scenarios.
- · High availability capabilities ensure maximum uptime. Buy two Firebox M470, M570 & M670s for an active/passive high availability pair and receive 50% off the cost of the second device.

Firebox	M470	M570	M670	
THROUGHPUT				
Firewall	19.6 Gbps	26.6 Gbps	34 Gbps	
Firewall (IMIX)	5.6 Gbps	7.6 Gbps	11.2 Gbps	
VPN (UDP 1518)	5.2 Gbps	5.8 Gbps	7.6 Gbps	
VPN (IMIX)	1.8 Gbps	2.0 Gbps	2.6 Gbps	
HTTPS (IPS enabled)	2.0 Gbps	3.4 Gbps	4.0 Gbps	
Antivirus	3.5 Gbps	5.4 Gbps	6.2 Gbps	
PS (fast/full scan)	5.7/3.0 Gbps	8.0/4.8 Gbps	10.4/5.6 Gbps	
UTM (fast/ full scan)				
CAPACITY	3.1/2.1 Gbps	4.4/3.5 Gbps	5.4/4.2 Gbps	
CAPACITY		-/		
Interfaces 10/100/1000*	8 (optional modules available)	8 (optional modules available)	8 (optional modules available)	
/O interfaces	1 SRL/2 USB	1 SRL/2 USB	1 SRL/2 USB	
Concurrent connections	3,800,000	8,300,000	8,500,000	
Concurrent connections (proxy)	310,000	710,000	920,000	
New connections per second	82,000	115,000	140,000	
VLANs	300	500	750	
WSM licenses (incl)	4	4	4	
TDR Host Sensors included	200	250	250	
Authenticated users limit	Unrestricted	Unrestricted	Unrestricted	
VPN TUNNELS				
Branch Office VPN	250	500	750	
Mobile VPN	250	500	750	
SECURITY FEATURES				
Firewall	Stateful packet inspection	, deep packet inspection, p	proxy firewall	
Application proxies	HTTP, HTTPS, FTP, DNS, TCP/UDP, POP3, POP3S, SMTP, IMAPS, and Explicit			
Threat protection	DoS attacks, fragmented & malformed packets, blended threats & more			
VoIP	H.323, SIP, call setup and session security			
Filtering options	Browser Safe Search, Goog	le for Business		
VPN & AUTHENTICATION		(C) 14 (C) 13 (C)		
Cloud providers	AWS (Static/Dynamic), Azure (Static/Dynamic)			
Encryption IPSec	AES 256-128 bit, 3DES, DES SHA-2, IKEv1/v2 , IKE pre-shared key, 3rd party cert,			
	Suite B			
Single sign-on		Windows, Mac OS X, mobile operating systems, SAML 2.0, RADIUS		
Authentication	RADIUS, LDAP, Windows Active Directory, VASCO, RSA SecurID, internal database, SAML 2.0, SMS Passcode			
MANAGEMENT				
Logging and notifications	WatchGuard, Syslog, SNMI	2 v2/v3		
User interfaces	Centralized console (WSM), Web UI, scriptable CLI			
Reporting	WatchGuard Dimension includes over 100 pre-defined reports, executive summary and visibility tools			
CERTIFICATIONS				
Security	Pending: ICSA Firewall, ICSA	IPSec VPN , CC EAL4+, FIPS	140-2	
Safety Network	NRTL/C, CB IPv6 Ready Gold (routing)			
Hazardous substance control	WEEE, RoHS, REACH			
NETWORKING	, ,			
Routing	Static, Dynamic (RGP4_OS	PF. RIP v1/v2). SD-WAN Dw	namic Path Selection	
High Availability	Static, Dynamic (BGP4, OSPF, RIP v1/v2), SD-WAN Dynamic Path Selection Active/passive, active/active with load balancing			
QoS	8 priority queues, DiffServ, modified strict queuing			
IP address assignment	Static, DHCP (server, client, relay), PPPoE, DynDNS			
-	Static, dynamic, 1:1, IPSec		rtual IP for server load	
NAT	balancing	, , , , , , , , ,		



PHYSICAL AND POWER SPECIFICATIONS

Product Dimensions 16.85" x 12.6" x 1.73" (42.8 x 32 x 4.4 cm)

Shipping Dimensions 22" x 21" x 5" (55.9 x 53.3 x 12.7 cm)

Cooling Fans

On/Off Switch

Power Supply

Shipping Weight 18 lbs (8.17 kg)

AC Power 100-240 VAC Autosensing

Power Consumption U.S. 75 Watts (max), 256 BTU/hr (max)

Rack Mountable 1U rack mount kit included

 ENVIRONMENT
 OPERATING
 STORAGE

 Temperature
 32° F to 104° F 0° C to 40° C
 14° F to 158° F 10° C to 70° C

 Relative Humidity
 5% to 90% non-condensing non-condensing
 5% to 90% non-condensing

Altitude 0 to 9,843 ft at 95° F 0 to 15,000 ft at 95° F (3,000 m at 35° C) (4,570 m at 35° C)

MTBF 51,644 hours @ 77° F (25° C)

STRONG SECURITY AT EVERY LAYER

Uniquely architected to be the industry's smartest, fastest, and most effective network security products, WatchGuard solutions deliver in-depth defenses against advanced malware, ransomware, botnets, trojans, viruses, drive-by downloads, data loss, phishing and much more.

 ${\it Total and Basic Security Suite packages are available on all Firebox solutions.}$

Features & Services	TOTAL SECURITY SUITE	Basic Security Suite
Intrusion Prevention Service (IPS)	✓	✓
App Control	✓	✓
WebBlocker	✓	✓
spamBlocker	✓	✓
Gateway AntiVirus	✓	✓
Reputation Enabled Defense (RED)	✓	✓
Network Discovery	✓	✓
APT Blocker	✓	
Data Loss Protection (DLP)	✓	
Threat Detection & Response	✓	
DNSWatch	✓	
Access Portal*	✓	
IntelligentAV*	✓	
Dimension Command	✓	
Support	Gold (24x7)	Standard (24x7)

For details, talk to your authorized WatchGuard reseller or visit www.watchguard.com.

* Firebox M470, 570 and 670 ship with one empty bay that can accommodate one of the following: 4 x 10 Gb fiber, 8 x 1 Gb fiber, or 8 x 1 Gb copper

Throughput rates are determined using multiple flows through multiple ports and will vary depending on environment and configuration. Max firewall throughput tested using 1518 byte UDP packets based on RFC 2544 methodology. UTM throughput is measured using HTTP traffic with AV, IPS, and Application Control enabled. Contact your WatchGuard reseller or call WatchGuard directly (1.800.734.9905) for help determining the right model for your network. Visit www.watchguard.com/sizing to access the online Product Sizing Tool.

802.3ad dynamic, static, active/backup

Port Independence, Multi-WAN failover and load balancing, server load

balancing, host header redirection, USB modem as a dedicated interface

Link aggregation

Other features